



SC Kronospan Sebes SA  
Str. Mihail Kogălniceanu 59 · Sebeş · 515800 · Alba  
Tel. +40 258 801100 · Fax +40 258 801199  
kronospan@kronospansebes.ro · www.kronospan.ro

SC Kronospan Sebes SA · Str. Mihail Kogălniceanu 59 · Sebeş · 515800 · Alba  
J01/604/1997 · RO 11358544  
Capital social 133 633 666,96 RON integral vărsat

Nr.17446/06.10.2011

## Raport trimestrial al emisiilor in aer

### SC KRONOSPAN SEBES SA

#### Trimestrul III - 2011

#### SECTIA CHIMICA

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Iulie	August	Septembrie
			Trimestrul III		
A1/ Instalatia de producere formaldehida	COT*	50	0,45	0,59	0,60
	formaldehida	5	0,84		
A2/ Instalatia de producere rasini pulbere	formaldehida	20	1,34		
	pulberi	20	0,80		
A3/ Exhaustare generala hala rasini pulbere	formaldehida	20	0,12		
	pulberi	20	1,01		
A4/ Centrala termica	CO	100	30,16		
	SO <sub>2</sub>	35	0		
	NO <sub>x</sub>	350	169,49		
	pulberi	5	0,76		

\*valoarea medie lunara - monitorizare on-line

#### SECTIA PAL

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Iulie	August	Septembrie
			Trimestrul III		
P17/ uscare aschii in uscator Krono-plus	COV	150	10,9		
	formaldehida	20	3,02	2,90	5,30
	pulberi*	20	6,96		
	CO	250	201,77		
	NO <sub>x</sub>	500	137,37		
P19/ exhaustare noxe presa din zona de evacuare	SO <sub>x</sub>	500	0,00		
	COV	150	58,0		
	formaldehida	20	10,38		
	pulberi	50	1,44		

\* monitorizare continua, trimestrial se efectueaza o monitorizare discontinua, masura R.I. nr.14384/12.08.2011

## SECTIA MDF

Sursa de emisie	Poluanti emisi	Limita admisa (mg/Nmc)	Iulie	August	Septembrie
			Trimestrul III		
P5/ ciclon 1 - uscare fibra	COV	150	58,6		
	formaldehida	20	18,61		
	pulberi*	50	27,15		
	NO <sub>x</sub>	500	30,10		
	SO <sub>x</sub>	500	0,00		
P5/ ciclon 2 - uscare fibra	COV	150	57,1		
	formaldehida	20	5,60		
	pulberi*	50	21,37		
	NO <sub>x</sub>	500	31,00		
	SO <sub>x</sub>	500	0,00		
P5/ ciclon 3 - uscare fibra	COV	150	57,2		
	formaldehida	20	16,94		
	pulberi*	50	30,82		
	NO <sub>x</sub>	500	46,01		
	SO <sub>x</sub>	500	0,00		
P5/ ciclon 4 - uscare fibra	COV	150	57,7		
	formaldehida	20	7,40		
	pulberi*	50	35,70		
	NO <sub>x</sub>	500	25,93		
	SO <sub>x</sub>	500	0,00		
P6/ evacuare noxe alimentare si evacuare presa placi MDF	COV	150	15,5		
	formaldehida	20	6,88		
	pulberi	50	1,41		

\* monitorizare continua, trimestrial se efectueaza o monitorizare discontinua, masura R.I. nr.14384/12.08.2011

## APA

Emisar/categoria apei evacuată	Indicator	Limita admisa (mg/l)	Iulie	August	Septembrie
			Trimestrul III		
Ape uzate evacuate in rețeaua de canalizare oraseneasca	temperatura	max 40°C	25		
	pH	6,5 – 8,5	8,02		
	suspensii	350	7,2		
	CBO5	300	5		
	CCO-Cr	500	171	<30	<30
	extractibile	30	<20(2,4)	<20(0,3)	<20(4,9)
	fenoli	30	0,056	0,005	<0,005
	NH <sub>4</sub>	30	13,5	0,127	0,2
Ape tehnologice conventional curate evacuate in emisar	temperatura	35°C	25		
	pH	6,5 – 8,5	7,4		
	suspensii	60	23,5		
	CBO5	25	16		
	CCO-Cr	125	47,6		
	extractibile	20	<20(0,3)		
	reziduu fix	2000	304		
	fenoli	0,3	<0,005		
NH <sub>4</sub>	3	2,59			

Director Productie

ADRIAN BACILA

